NW Cor. Sec. 30
Fd. I.P. in md. of stone — 73.7

3.64 — Fd 1"x2" hub in place - old, tack missing, but position on hub evident - identified as E.O.P. 1949 R by J.W.P.

Sec. Cor 24 | 19 / 25 | 30

W. 1/4 Cor. Sec 30
Fd. stone m'k'd. 1/4 on E. face — 60.1

W. line sec. 30 verified as straight in field.
Angle at N.W. Cor. 31 turned from N.W. Cor. Sec. 30 to stone for S.W. Cor Sec. 31 as shown.

1/4 Cor.

S.W. Cor Sec. 30
Fd I.B. flush w/paving — 46.24

3.52 — Fd 1X2 hub in place. Identified as P.O.T - 1949 R by J.W.P.

25 | 30 / 36 | 31

0°12'07"

N

R2

NOTE 1

S.W. Cor. Sec. 31, T.3N, R.1E.
Fd. stone 2½' below ground.
R in 1949 by J.W.P. shows 1" I.P. found 3.3' W. of his R. Stone was found by Arizona Surveying Service from ties shown by Maricopa Co. Highway Dept. and described as old ties.
Fd. stone is properly "hashmarked" w/x on top added. It is the approx. size of the granite stone set by W.H. Pierce in Jan. 1867 for B.L.M.,

1.1 stone

Angle shown at the S.W. Cor 31 is calc. from a line over the stone at the S.W. Cor. Sec. 31 and the N.W. Cor. Sec. 31 produced south to the S.W. Cor. Sec. 1 & the fallings taken to the corner from the produced line

0°29'

36 | 31 / 1 | 6

1.17

S.W. Cor. Sec. 6, T.2N, R.1E.
Fd. B.C. in paving (Glendale Ave.) 1949 R by J.W.P. passes over B.C.
B.C. checks old ties to corner from J.W.P. records.

0 B.C. 2°

R2

NOTE

R1 was run from the N.W. Cor Sec. 12 over the B.C. & I.P. for W 1/4 Cor. Sec. 1 South to the S.E. Cor. Sec. 12 & then produced N. to the S.W. Cor. Sec. 31 giving the fallings shown when positioned over the N.W. Cors Secs. 7 & 1, T.2N, R.1E.

R1

12 | 6 / 7 B.C.

W 1/4 Sec. 7 · Fd. 1" I.P. w/stone set alongside in md. of stone.

0 I.P. 3.4

0 1" I. 1.4

NOTE 1, CONT.:
and fd. in position by A.S. Colton in Sept. 1894 for B.L.M.
The fd. stone is red malapai and is not believed to be the original cor. However it has been set and coincides very closely in location to the I.P. fd. by J.W. Padgett in 1949; which, from called location, may have been placed from ties to the stone location.
REF: U.S. BUR. LD. MGMT field notes, books 1357 & 1711

S.W. Cor Sec. 7 · Fd. 1" I.P.

0.95
5° 0 I.P.

12.7 / 13.8 2.8

E 1/4 Cor. Sec. 18 · Fd C.I.P.
0.8' high - tapered w/0.17 dia. top set at W. side of fence corner post. 1949 R by J.W.P. passed this cor. 0.17 to the E. of & C.I.P. for corner.

Not to scale

REGISTERED LAND SURVEYOR
CERTIFICATE EXPIRES
EUGENE V. SKELLEY
DEC. 31, 1960
ARIZONA U.S.A.

R1 represents findings in field by W.H. Bartlett, H.L. Meredith & E.V. Skelley in Oct. 1959
R2 represents Skelley's retracement of a line run by J.W. Padgett, R.P.E. in Aug. 1949 which recorded corners found and re-set at that time (R2 was run in Oct, 1959.)
R2 was run over the W. 1/4 Cor. of Sec. 18 & a point set 5° W. of the S.W. Corner Sec 7 and produced N. to the N.W. Cor. of Sec. 30 as shown.

I hereby certify that the data shown hereon is a correct summary of the findings in the field by Arizona Surveying Service & W.H. Bartlett, R.P.E.

ARIZONA SURVEYING SERVICE

Eugene V. Skelley

DIN # 58273-1