M-S.87°53'00"E., 2726.27' (N.W. Cor. Sec. to N.1/4 Cor. Sec.)

M-1318.28'

Harrington Survey N.W. Cor. to N.E. Cor., S.87°53'E., Assumed This Survey, S.87°52'01"E.

Brass Cap Set By G.P.Harrington, Cadastral Surveyor According to Official B.L.M. Notes Dated 1919.

R-S.87°53' NOT E. 2641.00'

U.S.R.S. Cor. Recited in Dkt. 335, Pg. 312, M.C.R. Searched for, Not Found This Survey.

CM- S.87°53'00"E., 1407.99'

Fd. Concr. Filled Iron Pipe Below Ground Surface For the N1/4 Cor. Sec. 33.

4.4' from Old 1937 Notes

M-S.87°51'02"E. 2725.26'

5.8'

Note: From B.L.M. N.E. Cor. Sec. 33 Shown Fd. concrete filled iron pipe 1.0' below surface in ditch bank (U.S.R.S. Cor.) N.47°19'32"W, 53.43' from B.L.M. Cor.

Fd. M.C.H. Dept. Brass Cap In Handhole verified as position accepted by Harrington in 1919 for the N.E. Cor. Sec. 33

R-S.0°18'E., 1265.92', CM., Meas Calcs., S.0°15'W., 1268.12'

CM-S.1°27'33"E., 2642.57' (Sec. Cor. to 1/4 Cor.)

1059.35'

1015.96'

CM-N.0°54'25"E.

Parcel 2
33.13 A.

Survey line shown in 1937 notes by others as part of control for survey of location of fence described in legal description recited in Dkt. 335, Pg. 312, M.C.R.

CM-N.0°36'24"W., 1322.98'

CM-1016.38'

CM-205.68'

Note: No corners have been set at this time and all topography shown except the approximate location of the fence along the northerly line of Parcel I is from 1970 notes. There are other improvements existing at that time and at present not shown hereon. All corners symbolized as found and set hereon refer to 1970 field work.

CM-S.87°53'00"E., 1434.84'

N.11°54'55"W. 29.84

44.00

Dirt Road

Parcel I
5.19 A.
CANAL R/W 0.27A
NET AREA=4.92 A.

R-S.80°18'E., 380.02'

R-S.81°58'E., 200.66'

LR-S.80°49'30"E., 200.43'

E. ST. JOHNS CANAL

Meas. Approx. 36" Through High Henry Brush = Calc. 37.7' from 1937 Notes By Others

R-N.89°50'E., 1299.90'

Mon. & Calcs. R-N.89°32'E., 1.25.98

Cor. Post Old Fence Fd. in Place This Survey.

W.1/4 Cor., Fd. Iron Pipe

R-S.85°08'30"E., 116.02'

R-S.86°09'E., 100.04'

R-S.84°33'E 100.00'

R-S.81°12'E., 84.11'

R-S.3°42'W., 18.00'

CM- 201.96'

CM- 61.45'

R- "S.88°35'30"E., 201.96', More or Less to the north-south mid-section line of Sec. 33."
CM- S.88°35'30"E., 263.41'

Note: S.1/4 Cor. Searched For-Not Found. Mid-Line Position Shown Is Based On Mid-distance Between Fd. S.W. Cor. and Fd. S.E. Cor. Sec. 33.

Note: Platting and calculation study of old 1937 notes by others indicates that the last course in the deed description is actually the distance to the intersection point of the deedline with the survey control line shown in the notes and plotted here for information purposes.

11.0'

REPORT OF SURVEY

OF

That Portion of the N.1/2, N.W.1/4, Sec. 33, T.1N., R.1E., G.& S.R.B.& M., Mar. Co., Az. Shown Hereon.

FOR

Mrs. SYBLE M. DeWITT
Tolleson, Arizona

N

Scale: 1"=50'

LEGEND

- ●= Monument Found
- ●= Iron Pipe or Iron Bar Found
- ○= 1/2" I.D. Iron Pipe Tagged L.S. 1681 Set This Survey
- R= Data From Maricopa County Records (Dkt. 335, Pg. 312 M.C.R.)
- CR= Calculated From R
- M= Measured in Field
- CM= Calculated From M
- -x-x-x- = Wire or Wood Fence
- -o-o-o- = Chain Link Fence
- ========= = Block or Stone Wall
- △= Angle point on Record Deed line not set
- D= Dirt Irr. Ditch
- CD= Concr. Lined Ditch

CERTIFICATION: This will certify that the survey shown hereon was done under my supervision between Feb. 20, 1970 and June 15, 1970.

Eugene P. Weeks
3487

ARIZONA SURVEYING SERVICE
2802 W. SOLANO DR. N., PHOENIX, ARIZONA
Drawing No. L-74-7810 Phone: 242-0539

DIN 59680