REPORT OF SURVEY

Of the N. ½, S.W. ¼, S.W. ¼, Sec. 35, T.3N., R.1E., G.&S.R.B.&M., EXCEPT those parcels described in Dkt. 4441, P. 389 & Dkt. 2971, P. 72, Mar. Co. Rec.

N. ¼ Cor. Sec. 35 Fd. Stone in Hand-Hole.

E. ¼ Cor. Sec. 35 Fd. Brass Cap in Hand-Hole

M. = N. 88°00'45" E., 2658.02' (1329.01')

W ¼ Cor. Sec. 35 Found Brass Cap in Hand-Hole

N.E. Cor. W½, S.W. ¼, Set ½" Iron Pipe 4" Down.

Center Sec. 35 Old C.S. gone. W.H. Bartlett notes called old cor set by inters. between ¼ Cors. Set ¾" I.P. 4" down by same method.

N.E. Cor., N½, S.W. ¼ S.W. ¼, Sec. 35

1317.21'

1317.41'

Set Concr. Nail N.W. Cor. N½, S.W. ¼, S.W. ¼, Sec. 35

R. = N. 87°59'25" E., 1330.8' — C.M. = N. 88°00'22" E., 1330.74' (Gross)

W. Line 40' Rd'wy Easement

R. = This portion of the East line, N½, S.W. ¼, S.W. ¼ = N. 0°0'25" W.

R.&M. 1322.56'

65'

7' high chain link fence

Docket 2084, Page 480 Recites N. 87°59'25" E. ~~993.22'~~ (ERROR), C.R. = N. 87°59'26" E. 991.11' — M. = N. 88°00'31" E. 991.10'

M. = 591.10'

M. = 400.00'

5' wide concrete lined irrigation ditch

426.84'

DOCKET 4441 PAGE 389

Old fence: irregular alignment. varies from 2' E. of line to 0.5' West of line

Δ1 582.53' N 40°53'50" E

PARCEL "B" AREA - 5.794 A.

PARCEL "A" AREA - 7.137 A.

N 2°24'W 535.87'

429.66'

M. = 536.06'

M. = S. 0°04'30" E.

2634.54'

Scale, 1" = 60'

Fence varies from line to 0.25' North of line and 0.30' West of line

Set concrete nail in paving

R. = N. 88°23'E, M. = N. 88°25'E, R. = M. = 357.6'

Fd. ½" Iron Bolt 6" down, 0.3' E. 0.25' S. of face Fence Cor. Post

Δ2

Δ3

Δ4

Δ5

Δ6

Δ7

Δ8

Δ9

Δ10

Δ11

Δ12

Δ13

Δ14

Δ15

Δ16

Δ17

Δ18

Δ19

Δ20

Δ21

Δ22

Δ23

Δ24

Δ25

Δ26

Δ27

Δ28

Δ29

Δ30

Δ31

Δ32

Δ33

Δ34

Δ35

Δ36

Δ37

Δ38

Δ39

Δ40

Δ41